

Technical note

Measurement of the screw-home motion of the knee is sensitive to errors in axis alignment

Stephen J. Piazza^{a,b,c,*}, Peter R. Cavanagh^{a,b,d,e,f}

^aCenter for Locomotion Studies, Pennsylvania State University, 29 Recreation Building, University Park, PA 16802 and Hershey, PA 17033, USA

^bDepartment of Kinesiology, Pennsylvania State University, 29 Recreation Building, University Park, PA 16802 and Hershey PA 17033, USA

^cDepartment of Mechanical & Nuclear Engineering, Pennsylvania State University, 29 Recreation Building, University Park, PA 16802 and Hershey PA 17033, USA

^dDepartment of Biobehavioral Health, Pennsylvania State University, 29 Recreation Building, University Park, PA 16802 and Hershey PA 17033, USA

^eDepartment of Medicine, Pennsylvania State University, 29 Recreation Building, University Park, PA 16802 and Hershey PA 17033, USA

^fDepartment of Orthopaedics and Rehabilitation, Pennsylvania State University, 29 Recreation Building, University Park, PA 16802 and Hershey PA, 17033, USA

Accepted 22 February 2000

Abstract

Measurements of joint angles during motion analysis are subject to error caused by kinematic crosstalk, that is, one joint rotation (e.g., flexion) being interpreted as another (e.g., abduction). Kinematic crosstalk results from the chosen joint coordinate system being misaligned with the axes about which rotations are assumed to occur. The aim of this paper is to demonstrate that measurement of the so-called “screw-home” motion of the human knee, in which axial rotation and extension are coupled, is especially prone to errors due to crosstalk. The motions of two different two-segment mechanical linkages were examined to study the effects of crosstalk. The segments of the first linkage (NSH) were connected by a revolute joint, but the second linkage (SH) incorporated gearing that caused 15° of screw-home rotation to occur with 90° knee flexion. It was found that rotating the flexion axis (inducing crosstalk) could make linkage NSH appear to exhibit a screw-home motion and that a different rotation of the flexion axis could make linkage SH apparently exhibit pure flexion. These findings suggest that the measurement of screw-home rotation may be strongly influenced by errors in the location of the flexion axis. The magnitudes of these displacements of the flexion axis were consistent with the inter-observer variability seen when five experienced observers defined the flexion axis by palpating the medial and lateral femoral epicondyles. Care should be taken when interpreting small internal–external rotations and abduction–adduction angles to ensure that they are not the products of kinematic crosstalk. © 2000 Elsevier Science Ltd. All rights reserved.

Keywords: Screw-home; Knee kinematics; Motion analysis; Flexion axis; Kinematic crosstalk

1. Introduction

External rotation of the tibia with respect to the femur that accompanies knee extension is commonly thought to occur in the normal knee. This motion, the so-called “screw-home” mechanism, is described as being generated by asymmetry between the femoral condyles. The medial condyle has been reported to be approximately 1.7 cm longer than its lateral counterpart (Nordin and Frankel, 1980) and external tibial rotation is presumed to

result from the tibia conforming to the femoral condyles as the knee extends. Screw home has been described as characteristic of healthy knee motion and its absence is often described as indicative of instability or joint damage such as meniscal tears (Nordin and Frankel, 1980; Tasker and Waugh, 1982; Turek, 1984). The perceived clinical importance of screw-home motion was underscored by Helfet (1974), who devised a test for its absence in patients, and by several investigators who have measured total knee replacement motions to determine whether normal screw-home motion was present (Stein et al., 1988; Nilsson et al., 1990; Kärrholm et al., 1994; Dennis et al., 1998).

Several authors have measured the transverse-plane rotations of the normal knee with varying results. Levens

* Correspondence address. Center for Locomotion Studies, Pennsylvania State University, 29 Recreation Building, University Park, PA 16802, USA. Tel.: +1-814-865-3413; fax: +1-814-863-4755.

E-mail address: sjp12@psu.edu (S.J. Piazza).

landmarks whose locations may be difficult to determine with sufficient accuracy. Until such a system is developed, small out-of-plane rotations that are measured along with large flexion angles should be regarded as suspect. Such rotations should be examined carefully to ensure that they are not the product of kinematic cross-talk before they are used as the basis for treatment decisions.

Acknowledgements

The authors wish to thank Jonathan Gimbel and Marc Peterman for constructing mechanical linkages and Nori Okita for assisting in the collection of kinematic data.

References

- Blankevoort, L., Huijskes, R., de Lange, A., 1988. The envelope of passive knee joint motion. *Journal of Biomechanics* 21, 705–720.
- Cappozzo, A., Catani, F., Della Croce, U., Leardini, A., 1995. Position and orientation in space of bones during movement: anatomical frame definition and determination. *Clinical Biomechanics* 10, 171–178.
- Challis, J.H., 1995. A procedure for determining rigid body transformation parameters. *Journal of Biomechanics* 28, 733–737.
- DeLuzio, K.J., Wyas, U.P., Li, J., Costigan, P.A., 1993. A procedure to validate three-dimensional motion assessment systems. *Journal of Biomechanics* 26, 753–759.
- Dennis, D.A., Komistek, R.D., Walker, S., Anderson, D.T., 1998. In: 44th Annual Meeting of the Orthopaedic Research Society, New Orleans.
- Grood, E.S., Suntay, W.J., 1983. A joint coordinate system for the clinical description of three-dimensional motions: application to the knee. *Journal of Biomechanical Engineering* 105, 136–144.
- Hallen, L.G., Lindahl, O., 1966. The screw home movement in the knee-joint. *Acta Orthopaedica Scandinavica* 37, 97–106.
- Helfet, A., 1974. *Disorders of the Knee*. J.B. Lippincott Co., Philadelphia.
- Kadaba, M.P., Ramakrishnan, H.K., Wootten, M.E., 1990. Measurement of lower extremity kinematics during level walking. *Journal of Orthopaedic Research* 8, 383–392.
- Kärrholm, J., Jonsson, H., Nilsson, K.G., Soderqvist, I., 1994. Kinematics of successful knee prostheses during weight-bearing: three-dimensional movements and positions of screw axes in the Tricon-M and Miller-Galante designs. *Knee Surgery, Sports Traumatology, Arthroscopy* 2, 50–59.
- Kärrholm, J., Selvik, G., Elmqvist, L.G., Hansson, L.I., 1988. Active knee motion after cruciate ligament rupture. *Stereoradiography. Acta Orthopaedica Scandinavica* 59, 158–164.
- Kettlekamp, D.B., Johnson, R.J., Smidt, G.L., Chao, E.Y.S., Walker, M., 1970. An electrogoniometric study of knee motion in normal gait. *Journal of Bone and Joint Surgery* 52-A, 775–790.
- Koh, T.J., Grabiner, M.D., De Swart, R.J., 1992. In vivo tracking of the human patella. *Journal of Biomechanics* 25, 637–643.
- Kurosawa, H., Walker, P.S., Abe, S., Garg, A., Huner, T., 1985. Geometry and motion of the knee for implant and orthotic design. *Journal of Biomechanics* 18, 487–499.
- Lafortune, M.A., Cavanagh, P.R., Sommer, H.J., Kalenak, A., 1992. Three-dimensional kinematics of the human knee during walking. *Journal of Biomechanics* 25, 347–357.
- Levens, A.S., Inman, V.T., Blosser, J.A., 1948. Transverse rotations of the segments of the lower extremity in locomotion. *Journal of Bone and Joint Surgery* 30A, 859–872.
- Li, X.M., Liu, B., Deng, B., Zhang, S.M., 1996. Normal six-degree-of-freedom motions of knee joint during level walking. *Journal of Biomechanical Engineering* 118, 258–261.
- Nilsson, K.G., Kärrholm, J., Ekelund, L., 1990. Knee motion in total knee arthroplasty. A roentgen stereophotogrammetric analysis of the kinematics of the Tricon-M knee prosthesis. *Clinical Orthopaedics and Related Research*, 147–161.
- Nordin, M., Frankel, V.H., 1980. In: Frankel, V.H., Nordin, M. (Eds.), *Basic Biomechanics of the Skeletal System*. Lea & Febiger, Philadelphia, pp. 113–148.
- Schmidt, R., Disselhorst-Klug, C., Silny, J., Rau, G., 1998. In *Proceedings of North American Congress of Biomechanics*, pp. 47–50.
- Shiavi, R., Limbird, T., Frazer, M., Stivers, K., Strauss, A., Abramovitz, J., 1987. Helical motion analysis of the knee — II. Kinematics of uninjured and injured knees during walking and pivoting. *Journal of Biomechanics* 20, 653–665.
- Stein, A., Fleming, B., Pope, M.H., Howe, J.G., 1988. Total knee arthroplasty kinematics. An in vivo evaluation of four different designs. *Journal of Arthroplasty* 3 (Suppl.) S31–S36.
- Tasker, T., Waugh, W., 1982. Articular changes associated with internal derangement of the knee. *Journal of Bone and Joint Surgery — British Volume* 64, 486–488.
- Trent, P.S., Walker, P.S., Wolf, B., 1976. Ligament length patterns, strength, and rotational axes of the knee joint. *Clinical Orthopaedics & Related Research*, 263–270.
- Turek, S.L., 1984. *Orthopaedics*. J.B. Lippincott Co., London.
- Woltring, H.J., 1994. 3-D attitude representation of human joints: a standardization proposal. *Journal of Biomechanics* 27, 1399–1414.